

DISINFECTANT



Global Excellence in Animal Health

BIMACIDE

BACTERICIDAL

VIRUCIDAL

FUNGICIDAL

Disinfection of walls, floors and other surfaces in the livestock industry



For disinfecting
• Surfaces
• Materials
• walls & footbaths

www.bimeda.com

BIMEDA LTD.

Funzi Road, Industrial Area. P.O. Box 30620-00100,

Nairobi, Kenya

Tel: +254 20 6537622-6 Fax: +254 20 6537628

BIMACIDE

DISINFECTANT

Composition:

Alkyldimethylbenzylammonium chloride 61.5 g/l glyoxal 19.8 g/l
 Glutaraldehyde 58.0g/l. Formaldehyde 84.4 g/l Isopropanol
 37.6 g/l

Uses: Disinfection of walls, floors and other surfaces in the industry and animal breeding.

Action: Bactericidal, fungicidal and virucidal (including avian influenza)

Directions for use:

Clean thoroughly the surfaces before applying a dilution of the disinfectant

Surfaced, materials & walls...	Foot baths	Fogging devices
Dilution: 0.5% to 1% (0.5 to 1 litre in 100 L water) Hand Sprayer: 1 Litre dilution per 3m ³ High pressure cleaner 1 L dilution per 2m ²	Dilution: 2% (2 L Bimacide in 100 L water) Refresh the disinfection foot bath every day.	Dilution 33% 1.5 L Bimacide in 3L water is sufficient for complete disinfection of a volume of 1000 m ²

Contact time: 15 minutes

Storage: Store in a well closed packing, protected from light in a ventilated area.

Toxicological groups: Quaternary ammonium compounds and aldehydes.

PROPERTIES

- Wide spectrum of action
- High efficacy at low concentration
- Biodegradation
- Chemically stable and non corrosive
- Effective even in presence of organic matter and hard water.



SAFETY PRECAUTION

- Do not breathe any vapour
- In case of contact with eye, rinse immediately with plenty of water and seek medical advice.
- Wear suitable protective clothing, gloves and eye face protective
- In case of emergency and if you feel unwell, seek medical advice immediately. (show the label where possible).
- Avoid release to the environment
- Refer to special instructions /safety data sheets
- In case of insufficient ventilation wear suitable respiratory equipment
- This material and its container must be disposed of as hazardous waste

Shelf life: 3 years

Packing

5 litres, 1 litre, 500ml, 250ml, 100ml

Manufactured by:

BIMEDA LTD.

Funzi Road, Industrial Area. P.O. Box 30620-00100, Nairobi, Kenya

Tel: +254 20 6537622-6 Fax: +254 20 6537628

